



Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11) Publication number: **0 414 549 B1**

(12)

## EUROPEAN PATENT SPECIFICATION

(45) Date of publication of patent specification: **07.12.94** (51) Int. Cl.<sup>5</sup>: **C11D 17/00**

(21) Application number: **90309273.2**

(22) Date of filing: **23.08.90**

The file contains technical information submitted  
after the application was filed and not included in  
this specification

(54) **Liquid cleaning compositions and suspending media.**

(30) Priority: **24.08.89 GB 8919254**

(43) Date of publication of application:  
**27.02.91 Bulletin 91/09**

(45) Publication of the grant of the patent:  
**07.12.94 Bulletin 94/49**

(64) Designated Contracting States:  
**AT BE CH DE DK ES FR GB GR IT LI LU NL SE**

(56) References cited:  
**EP-A- 0 125 711**  
**FR-A- 2 416 261**  
**GB-A- 2 179 053**

(73) Proprietor: **Albright & Wilson Limited**  
**210-222 Hagley Road West**  
**Oldbury Warley West Midlands B69 4PR (GB)**

(72) Inventor: **Hawkins, John**  
**Moorfield,**  
**Goosebutts**  
**Keekle, Cleator Moor, Cumbria CA25 5QY**  
**(GB)**  
Inventor: **Nicholson, William John**  
**117 Nimmings Road**  
**Halesowen, West Midlands B62 9JH (GB)**

(74) Representative: **Savidge, Roger Gordon Madg-**  
**wick et al**  
**Albright & Wilson Limited**  
**Patents Department**  
**210-222 Hagley Road West**  
**Oldbury**  
**Warley, West Midlands B68 0NN (GB)**

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid (Art. 99(1) European patent convention).

**EP 0 414 549 B1**

## Descripti n

INTRODUCTION

5 The present invention relates to liquid media, which are capable of suspending particulate solids or dispersed liquids or gases and which are especially useful as cleaning compositions.

The invention is applicable for example to the formulation of liquid dishwashing compositions, hard surface cleaners coal/water slurries and phosphate free laundry detergents and also provides suspending media for other solids such as pesticides, explosives, pigments, ceramics, catalysts or pharmaceuticals.

10

DEFINITIONS

The following terms in parenthesis are used herein in the sense hereafter defined unless a contrary meaning is stated or required by the context.

15 "Functional Material" means any substantially water insoluble solid, liquid or gas which is to be suspended in an aqueous composition in order to perform a useful function when the composition is used. Examples of functional materials include water insoluble builders such as zeolites, silicone antifoam oils, solid pesticides, ceramics, catalysts, pigments, liquified or compressed gases for use as foaming agents, coal and pharmaceuticals.

20 "Surfactant" is an organic compound having a hydrophilic and a hydrophobic portion, which substantially lowers the surface energy of a water/oil interface when present in relatively low concentrations. "Surfactant", as used herein, includes not only such conventional surfactants as C<sub>6</sub>-20 alkyl benzene sulphonates, alkyl sulphates, alkyl ethoxylates and alkyl trimethylammonium salts, but also such amphiphilic compounds as C<sub>6</sub>-20 fatty alcohols and fatty acids which are not normally classed as surfactants on account of their low solubility, when the latter are solubilised by the presence of a cosurfactant.

25 "Electrolyte" is used herein to denote those ionic compounds which dissociate at least partially in aqueous solution to provide ions, and which at the concentrations present tend to lower the total solubility (including micellar concentration) of surfactants in such solutions by a "salting out" effect.

References herein to the Electrolyte content or concentration refer to the total dissolved Electrolyte, 30 including any dissolved Functional Material, if such material is also an Electrolyte, but excludes any suspended solid.

"Substantially free from Electrolyte" means containing insufficient Electrolyte to destabilise the suspension. Typically this implies compositions containing less than 0.5%, preferably less than 0.2% e.g. less than 0.1% by weight, based on the weight of the composition, of Electrolytes added as such, other than any 35 "tramp" electrolyte unavoidably present in the surfactant, or in the suspended Functional Material or any dissolved portion of the suspended solid. "Substantially insoluble" means having a solubility in water less than 2% by weight at 20 °C, in the case of ionisable compounds or less than 20% preferably less than 10% e.g. less than 5% in the case of non-ionic compounds.

"Bilayer" includes a layer of surfactant approximately two molecules thick, which is formed from two 40 adjacent parallel layers, each comprising surfactant molecules which are disposed such that the hydrophobic portions of the molecules are located in the interior of the Bilayer and the hydrophilic portions are located on its outer surfaces. "Bilayer" is also used herein to include interdigitated layers, which are less than two molecules thick. An interdigitated layer may be regarded as a Bilayer in which the two layers have interpenetrated allowing at least some degree of overlap between the hydrophobic portions of the molecules 45 of the two layers.

"Spherulite" means a spherical or spheroidal body having dimensions, of from 0.1 to 50 µm. Spherulites may sometimes be distorted into prolate, oblate, pear or dumbell shapes. "Vesicle" means a Spherulite containing a liquid phase bounded by a Bilayer. "Multiple Vesicle" means a Vesicle which contains one or more smaller Vesicles.

50 "Lamellar Phase" means a hydrated solid, or liquid crystal phase in which a plurality of Bilayers are arranged in a substantially parallel array, separated by layers of water or an aqueous solution, and having a sufficiently regular lattice spacing of from 25 to about 150 nm to be readily detectable by neutron scattering or X-ray diffraction when present as a substantial proportion of a composition. As used herein the expression excludes concentric Multiple Vesicles.

55 "G" phase refers to a liquid crystal Lamellar Phase, of the type also known in the literature as "neat" phase or "lamellar" phase. The "G" phase for any given surfactant or surfactant mixture normally exists in a narrow range of concentrations. Pure "G" phases can normally be identified by examination of a sample under a polarising microscope, between crossed polarisers. Characteristic textures are observed in accor-

dance with the classic paper by Rosevear, JAOCS Vol. 31 P628 (1954) or in J. Colloid and Interfacial Science, Vol. 20 No. 4, P.500 (1969). "G" phases normally exhibit a repeat spacing of from 50 to 70 nm, in X-ray diffraction or neutron scattering patterns. "Expanded G phase" means a "G" phase with a repeat spacing of 110 to 150 nm.

5 "Spherical G Phase" means Multiple Vesicles formed from substantially concentric shells of surfactant Bilayer alternating with aqueous phase with a "G" phase or Expanded G phase spacing. Typically conventional G phases may contain a minor proportion of Spherical G Phase.

"Lye" means an aqueous liquid phase containing Electrolyte, which phase separates from, or is interspersed with, a second liquid phase containing more Active Ingredient and less Electrolyte than the Lye phase.

10 "Lamellar Composition" means a composition in which a major part of the surfactant is present as a Lamellar Phase, or in which a Lamellar Phase is the principal factor inhibiting sedimentation. "Spherulitic Composition" means a composition in which a major part of the surfactant is present as Spherulites, or which is principally stabilised against sedimentation by a spherulitic surfactant phase.

15 "Solubility Parameter" is as defined and described in section VII p. 519 of "The Polymer Handbook".

### BACKGROUND

20 Liquid cleaning preparation often require the presence of suspended solids. For example hard surface scouring creams require the presence of abrasives and effective laundry detergents require cost effective builders, which may be sparingly soluble or insoluble in water. There is also a substantial demand in many fields of activity for fluid systems to disperse a variety of functional materials which may be solid, liquid or gaseous and which are not easily dissolved or dispersed in aqueous media.

25 In the case of scouring creams and liquid laundry detergents these problems have been solved by utilising the interaction between electrolytes and surfactants to provide solid suspending structures based on thixotropic dispersions or interspersions of surfactant mesophases with aqueous electrolyte solutions.

30 GB 2,123,846 describes the use of mesophase surfactant interspersed with an electrolyte solution. A different structure, also referred to in GB 2 123 846, and present, although not specifically identified, in formulations exemplified in a number of other publications, comprises an array of spherulites, each having a plurality of concentric shells of surfactant alternating with layers of electrolyte solution. Patent specifications which describe formulations which probably exhibit spherulitic or lamellar structure include:

35

40

45

50

55

	AU 482374	GB 855679	US 2920045
	AU 507431	GB 855893	US 3039971
	AU 522983	GB 882569	US 3075922
5	AU 537506	GB 943217	US 3232878
	AU 542079	GB 955081	US 3235505
	AU 547579	GB 1262280	US 3281367
	AU 548438	GB 1405165	US 3328309
	AU 550003	GB 1427011	US 3346503
10	AU 555411	GB 1468181	US 3346504
		GB 1506427	US 3351557
	CA 917031	GB 1577120	US 3509059
		GB 1589971	US 3374922
	CS 216492	GB 2600981	US 3629125
15		GB 2028365	US 3638288
	DE A1567656	GB 2031455	US 3813349
		GB 2054634	US 3956L58
	DE 2447945	GB 2079305	US 4019720
			US 4057506
20	EP 0028038	JP-A-52-146407	US 4107067
	EP 0038101	JP-A-56-86999	US 4169817
	EP 0059280		US 4265777
	EP 0079646	SU 498331	US 4279786
	EP 0084154	SU 922066	US 4299740
25	EP 0103926	SU 929545	US 4302347
	FR 2283951		

although in most instances the structures which would have been present in the formulations as described were insufficiently stable to maintain solids in suspension. GB 2153 380 describes the spherulitic structure and methods for preparing a close packed, space filling, structure, sufficiently robust to withstand various forms of shear and temperature stress, but sufficiently mobile to be readily poured. The method requires optimising electrolyte concentrations within close limits.

In our pending British Patent Application No. 89 06234.3 we have described the use of structured surfactant systems for the support of pesticides.

All the foregoing art requires the presence of substantial concentrations of electrolyte, typically around 12%, in order to form a stable supporting structure by interaction with the surfactant.

This does not necessarily represent a problem in formulations where the presence of electrolytes is desired to achieve particular performance criteria e.g. in phosphate, carbonate and/or silicate built detergents.

However the need to incorporate electrolytes represents a significant restriction on the ability to prepare stable formulations for a variety of special purposes for which electrolytes are undesirable. It is known that some surfactants form mobile lamellar mesophases in the absence of electrolyte. The preparation of 'G' phases from certain surfactants and surfactant mixtures has been described, for example in GB 1538 199, GB 1488352, GB 1533 851, GB 2021 141, GB 2013 235, GB 2031 941, GB 2023 637 AND GB 2022 125. In all of these references a lamellar mesophase is formed by a surfactant or mixture of surfactants in the absence of electrolyte within a narrow range of concentrations. Attempts to suspend effective quantities of solid particles, such as builders, in lamellar ("G") mesophases as described in the foregoing references have resulted in the formation of immobile pastes.

## 50 THE INVENTION

We have now discovered that certain surfactants form structured systems, such as spherulitic or dispersed lamellar phases in the substantial absence of electrolyte, which are capable of supporting particulate solids to form mobile suspensions. In particular we have discovered that mixed surfactants having a mean solubility parameter in the range 10 to 12 tend to form spherulitic systems in the absence of added electrolyte and at concentrations typically in the range 8 to 25% by weight.

These suspensions are of value for a variety of applications, such as in automatic dishwashing compositions, hard surface cleaners, phosphate-free laundry detergents and pesticide suspensions.

Our invention therefore provides a composition comprising : water; a surfactant or mixture of surfactants present in a concentration sufficient to form a spherulitic or dispersed lamellar phase in the absence of Electrolyte; and a substantially insoluble functional material, suspended in the composition; said composition being substantially free from Electrolyte.

- 5 According to a preferred embodiment the surfactant comprises at least one surfactant with a solubility parameter greater than 13 and at least one surfactant with a solubility parameter below 10, the relative proportions being such as to provide a mean solubility parameter for the mixture between 10 and 13.

#### SURFACTANT

10

The surfactant system according to the present invention may be any surfactant, mixture of surfactants or mixture of surfactant and hydrotrope that forms a solid-supporting spherulitic or mobile lamellar phase in the absence of added Electrolyte.

- The surfactants or surfactant mixtures that can be used according to the present invention are typically 15 those that form a 'G' phase at ambient temperature, but, preferably, do not form an  $M_1$  phase. Generally speaking the aqueous surfactant system has a cloud point greater than  $30^\circ\text{C}$ , more usually greater than  $40^\circ\text{C}$  and preferably greater than  $50^\circ\text{C}$ . Aqueous surfactant systems having a cloud point above  $60^\circ\text{C}$  are especially suitable. Alternatively or additionally the surfactant may have an inverse cloud point below  $30^\circ\text{C}$ , more usually below  $20^\circ\text{C}$ , especially below  $10^\circ\text{C}$ , preferably below  $0^\circ\text{C}$ . Surfactants with an inverse cloud 20 point below  $-10^\circ\text{C}$  are especially useful. Inverse cloud points are typical of some nonionic surfactants, in which increasing temperature tends to break the hydrogen bonds responsible for hydration of the hydrophilic part of the molecule, thus rendering it less soluble. Normal cloud points are more typical of anionic or cationic surfactants. Mixtures of anionic and nonionic surfactant may show a cloud point and/or an inverse cloud point.

- 25 It is usually preferred that the surfactant should be present in a concentration of at least 1% eg at least 3% by weight of the composition more usually above 5%, especially above 8% and preferably above 10%. A typical range of concentrations of the surfactants is from 7 to 50% more usually 10 to 40% preferably 15 to 30%. Other concentration of surfactants which may be used are 1-30% eg 2-15% by weight of the composition.

- 30 Concentrations of surfactant above 60% are possible but very unlikely to be commercially viable as suspending media at least for the majority of foreseeable uses of the invention.

- Particularly preferred are nonionic and mixed nonionic surfactants, especially mixtures of fatty alcohol ethoxylates and mixtures of fatty alcohol ethoxylates with fatty acid ethoxylates or mixed ethoxylated/propoxylated alcohols and fatty acids ethoxylates. For example mixtures comprising one or more  $\text{C}_{10}$  to 35  $\text{C}_{20}$  average fatty alcohols and or fatty acids alkoxyated with from 5 to 15 ethyleneoxy and/or propyleneoxy groups, are especially useful. Other non-ionic surfactant which may be used include alkoxyated alkyl-phenols, alkoxyated amines, alkoxyated sorbitan or glycerol esters of fatty acids, and alkanolamides such as coconut mono- di-or tri-ethanolamide and mixtures thereof.

- Anionic surfactants of particular value include; alkyl benzene sulphonates, especially the lower (e.g. 40  $\text{C}_{1-6}$ ) amine salts such as isopropylamine  $\text{C}_{10-14}$  alkyl benzene sulphonate, fatty alkyl polyethyleneoxy sulphates, fatty alkyl polyethyleneoxy phosphates, alkyl sulphates, especially ammonium or lower amine salts, sulposuccinates, sulposuccinamates, isethionates, taurides, soaps, paraffin sulphonates, olefin sulphonates and ester sulphonates. The cation of the anionic surfactant may, for example, be sodium, potassium or lithium, or less preferably calcium or magnesium, but most preferably an ammonium or a 45 primary, secondary, tertiary or quaternary  $\text{C}_{1-6}$  total alkylammonium such as methylammonium, dimethylammonium, trimethylammonium, tetramethylammonium, ethyl ammonium, propylammonium, isopropylammonium, mono ethanolammonium, diethanolammonium or triethanolammonium.

The surfactant may comprise an amine oxide or alkylated amine oxide or an amphoteric surfactant such as a betaine or sulphobetaine.

- 50 The surfactant may comprise a cationic surfactant, such as a fatty alkyl tris (lower alkyl) ammonium salt (eg tallowyl trimethyl ammonium chloride) or benzalkonium salt e.g. lauryl benzyl bis methyl ammonium chloride, an amido amine, quaternised amido amine, imidazoline, ethoxylated imidazoline or quaternised imidazoline.

- The anion of the cationic surfactant may, for instance, be a halide such as chloride, fluoride or bromide, 55 a methosulphate, or a carboxylate anion such as formate, acetate, citrate or lactate.

Typically when a surfactant is to be used which has a Solubility Parameter greater than 12 it should be mixed with a surfactant having a solubility parameter less than 11 and vice versa, the relative proportions being selected such that the mean solubility parameter of the mixture is between 10 and 13, preferably

between 11 and 12.

A particular feature of the invention is the ability to utilise compounds which on account of their low solubility in water are not usually effective as surfactants and are not usually classified as such but which are useful surfactants in the presence of cosurfactants which may then be used to form spherulitic compositions. Typically such compounds are amphiphiles having a hydrophobic group such as an alkyl, alkenyl or alkaryl group comprising 6 to 22 aliphatic carbon atoms and a polar group such as a hydroxyl, carboxyl, carbonyl, ester, amino, benzylamino, alkylamino, pyridine, amido, nitro, cyano or halo group. Typical examples are fatty alcohols such as octyl, lauryl, cetyl or stearyl alcohol, fatty acids such as decanoic, lauric, stearic, coconut, palmitic or behenic acids, unsaturated acids such as oleic, linoleic or linolenic acids, phenols such as nonyl phenol, halides such as p-chloro-dodecyl benzene, ketones such as dodecyl cyclohexanone, aldehydes such as octanal, amines such as coconut fatty amine, dodecyl dimethylamine, glycerides such as olive oil or glyceryl distearate and heterocyclics such as 4-lauryl pyridine. Typically the amphiphile is less than 1% by weight soluble in water, e.g. less than 0.5% especially less than 0.2% eg. less than 0.1%.

#### SUSPENDED MATERIAL

The suspended material may, for example, comprise a water insoluble detergent builder such as a zeolite or a particulate ion exchange resin, an inert abrasive such as calcite, talc or a substantially water insoluble pesticide, catalyst, ceramic, pharmaceutical or pigment or a silicone oil, or substantially water insoluble gas. The particle size is not usually critical. Typically particles of from 1 to 100 microns may be suspended e.g. 5 to 70 micron especially 10 to 50 micron.

The solid may be present in any concentration from 2% to 85% but preferably 10% to 60% especially 15% to 40%.

#### STRUCTURE

The surfactant is preferably present in a sufficient concentration to form a stable spherulitic phase. Some surfactants form stable spherulitic structures at concentrations in the range 4 to 20% others require higher concentration in the range 25 to 50% by weight. The spherulitic structure comprises closely packed spherulites each of which comprises concentric bilayer shells of surfactant alternating with water. Typically the successive shells have a repeat spacing of 110 to 150 nm. Alternatively the surfactant may form an open expanded lamellar ("G" phase) structure with a similar repeat spacing. Suitable hydrotropes include lower alkyl benzene sulphonate such as sodium toluene sulphonate, sodium xylene sulphonate or sodium cumene sulphonate, a lower molecular weight alcohol (e.g. C<sub>4-10</sub> alcohol) or alcohol ethoxylate.

The invention is illustrated by the following examples:

#### Example 1

An automatic dishwashing composition comprises:

	% wt/wt
Lauric acid 9 mole ethoxylate	6.6
cetyl/oleyl alcohol 6 mole ethoxylate	13.3
"WESSALITH" P (Trademark) zeolite	20
perfume	0.1
silicone antifoam	0.2
water	balance

The product is a pourable, non-sedimenting composition with good dishwashing performance and low foaming characteristics.

Example 2

An abrasive hard-surface cleaner comprises:

	% wt/wt
cetyl/oleyl alcohol 6 mole ethoxylate	6.6
lauric acid 9 mole ethoxylate	1.4
"DURCAL" 15 (Trademark) calcite	50
perfume	0.1
water	balance

The product is a pourable, non-sedimenting cream with good scouring and cleaning properties.

Example 3

A coal/water slurry comprises:

	% wt/wt
cetyl/oleyl alcohol 6 mole ethoxylate	2
lauric acid 9 mole ethoxylate	1
powdered coal	75
water	balance

The product was a non-sedimenting pumpable slurry.

Example 4

A pesticide suspension comprises:

	% wt/wt
isopropylamine C <sub>10-14</sub> alkylbenzene sulphonate	10
phenmedipham	20
water	balance

The product is a pourable non-sedimenting composition.

Example 5

A pesticide suspension comprises:

	% wt/wt
"EMPICOL" 0216 (Trademark) alkyl ethoxy phosphate ester	10
phenmedipham	20
water	balance

The product is a pourable, non-sedimenting composition.

Example 6

A pesticide suspension comprises:

5		% wt/wt
	"EMPICOL" 0216 (Trademark) alkyl ethoxy phosphate ester	10
	mandeb	20
10	water	balance

The product is a pourable, non-sedimenting composition.

Example 7

15 Mixtures of lauryl alcohol, triethanolamine dodecyl benzene sulphonate and water formed spherulitic suspending media at concentrations between 5 and 22% total surfactant and weight ratios of sulphonate to alcohol greater than 4.8:6.2.

Example 8

20 Mixtures of water, olive oil and isopropylamine secondary C<sub>12</sub> alkyl benzene sulphonate formed spherulitic suspending systems at concentrations between 9 and 21% total surfactant and weight ratios of sulphonate to olive oil greater than 4.5:6.5.

Example 9

25 Mixtures of water, octanol and triethanolamine C<sub>12</sub> linear alkyl benzene sulphonate formed spherulitic suspending systems at total surfactant concentrations of 5 to 20% by weight and ratios of sulphonate to octanol greater than 5.8 to 4.2.

Example 10

30 Mixtures of water, oleic acid and triethanolamine C<sub>12</sub> linear alkylbenzene sulphonate at a total surfactant concentration greater than 12% by weight and a weight ratio of sulphonite to acid between 4.5:5.5 and 7:3 formed spherulitic suspending media.

**Claims**

- 40 1. A mobile liquid composition comprising: water; a surfactant or mixture of surfactants present in a concentration sufficient to form a mobile spherulitic or dispersed lamellar phase in the absence of Electrolyte; and a substantially water insoluble functional material, suspended in the composition, said composition being substantially free from Electrolyte.
- 45 2. A composition according to claim 1 wherein said surfactant forms a "G" phase at ambient temperature, but not an M<sub>1</sub> phase.
3. A composition according either of claims 1 and 2 wherein the mixture of water and surfactant has a cloud point above 30 °C.
- 50 4. A composition according to claim 3 wherein the mixture of surfactant and water has a cloud point greater than 40 °C.
5. A composition according to any foregoing claim wherein the mixture of surfactant and water has an inverse cloud point below 30 °C.
- 55 6. A composition according to claim 5 wherein the mixture of surfactant and water has an inverse point below 10 °C.



7. A composition according to any foregoing claim wherein the surfactant is present in a concentration greater than 5% by weight of the composition.
8. A composition according to claim 7 wherein the surfactant is present in a proportion of from 7 to 50% by weight of the composition.
9. A composition according to any foregoing claim wherein the surfactant comprises one or more C<sub>10</sub> to C<sub>20</sub> average fatty alcohols alkoxylated with from 5 to 15 ethylenoxy and/or propyleneoxy groups.
10. A composition according to any foregoing claim wherein the surfactant comprises a C<sub>1-6</sub> amine C<sub>10-14</sub> alkyl benzene sulphonate.
11. A composition according to claim 10 wherein said C<sub>1-6</sub> amine is isopropylamine or triethanolamine.
12. A composition according to any foregoing claim comprising a mixture of surfactants having a mean solubility parameter between 10 and 13.
13. A composition according to to claim 12 wherein said surfactants have a mean solubility parameter between 11 and 12.
14. A composition according to any foregoing claim comprising a mixture of a surfactant having a solubility parameter greater than 12 and surfactant having a solubility parameter less than 11.
15. A composition according to any foregoing claim comprising a surfactant having a water solubility less than 1% weight and sufficient cosurfactant to solubilise it to the extent of at least 5% by weight.

#### Patentansprüche

1. Eine mobile, flüssige Zusammensetzung enthält
  - Wasser;
  - ein Tensid (bzw. oberflächenaktives Mittel) oder ein Gemisch aus Tensiden, wobei das oder die Tensid(e) in einer Konzentration vorhanden ist/sind, die ausreicht, in Abwesenheit von Elektrolyt eine sphärolithische Phase oder eine dispergierte lamellare Phase zu bilden; und
  - ein funktionelles Material, das in Wasser im wesentlichen unlöslich ist, und das in der Zusammensetzung suspendiert ist;wobei diese Zusammensetzung im wesentlichen frei von Elektrolyt ist.
2. Die Zusammensetzung nach Anspruch 1, dadurch gekennzeichnet, daß das Tensid bei Raumtemperatur eine "G"-Phase, jedoch keine M<sub>1</sub>-Phase bildet.
3. Die Zusammensetzung nach Anspruch 1 oder 2, dadurch gekennzeichnet, daß die Mischung aus Wasser und Tensid einen Trübungspunkt oberhalb 30° C aufweist.
4. Die Zusammensetzung nach Anspruch 3, dadurch gekennzeichnet, daß die Mischung aus Tensid und Wasser einen Trübungspunkt oberhalb 40° C aufweist.
5. Die Zusammensetzung nach einem der Ansprüche 1 bis 4, dadurch gekennzeichnet, daß die Mischung aus Tensid und Wasser einen inversen Trübungspunkt unterhalb 30° C aufweist.
6. Die Zusammensetzung nach Anspruch 5, dadurch gekennzeichnet, daß die Mischung aus Tensid und Wasser einen inversen Trübungspunkt unterhalb 10° C aufweist.

7. Die Zusammensetzung nach einem der Ansprüche 1 bis 6,  
dadurch gekennzeichnet, daß  
das Tensid in einem Anteil vorhanden ist, der mehr als 5 Gew.-% der Zusammensetzung ausmacht.
- 5 8. Die Zusammensetzung nach Anspruch 7,  
dadurch gekennzeichnet, daß  
das Tensid in einem Anteil vorhanden ist, der 7 bis 50 Gew.-% der Zusammensetzung ausmacht.
9. Die Zusammensetzung nach einem der Ansprüche 1 bis 8,  
10 dadurch gekennzeichnet, daß  
das Tensid ein oder mehrere mittlere  $C_{10-20}$ -Fettalkohole ist, die mit 5 bis 15 Mol Äthylenoxyd-  
Gruppen und/oder Propylenoxyd-Gruppen pro Mol Fettalkohol alkoxyliert sind.
10. Die Zusammensetzung nach einem der Ansprüche 1 bis 9,  
15 dadurch gekennzeichnet, daß  
das Tensid aufweist ein  $C_1-6$ -Amin- $C_{10-14}$ -Alkylbenzol-Sulfonat.
11. Die Zusammensetzung nach Anspruch 10,  
dadurch gekennzeichnet, daß  
20 das  $C_1-6$ -Amin Isopropylamin oder Triäthanolamin ist.
12. Die Zusammensetzung nach einem der Ansprüche 1 bis 11,  
dadurch gekennzeichnet, daß  
die Zusammensetzung ein Gemisch aus Tensiden enthält, und dieses Tensidgemisch einen mittleren  
25 Löslichkeitsparameter zwischen 10 und 13 aufweist.
13. Die Zusammensetzung nach Anspruch 12,  
dadurch gekennzeichnet, daß  
das Tensidgemisch einen mittleren Löslichkeitsparameter zwischen 11 und 12 aufweist.  
30
14. Die Zusammensetzung nach einem der Ansprüche 1 bis 13,  
dadurch gekennzeichnet, daß  
die Zusammensetzung ein Gemisch aus Tensiden enthält; und wenigstens ein Tensid einen Löslich-  
keitsparameter größer 12 und wenigstens ein weiteres Tensid einen Löslichkeitsparameter kleiner 11  
35 aufweist.
15. Die Zusammensetzung nach einem der Ansprüche 1 bis 14,  
dadurch gekennzeichnet, daß  
das Tensid in Wasser eine Löslichkeit kleiner 1 Gew.-% aufweist; und ein Co-Tensid in einer  
40 ausreichenden Menge vorhanden ist, um das eigentliche Tensid in Wasser bis zu einer Löslichkeit von  
wenigstens 5 Gew.-% zu solubilisieren.

#### Revendications

- 45 1. Composition liquide mobile comprenant: de l'eau, un tensioactif ou un mélange de tensioactifs présent  
à une concentration suffisante pour former une phase sphérolithique mobile ou lamellaire dispersée en  
l'absence d'électrolyte et une matière fonctionnelle essentiellement insoluble, en suspension dans  
ladite composition, laquelle est essentiellement exempte d'électrolyte.
- 50 2. Composition selon la revendication 1, dans laquelle ledit tensioactif forme une phase "G", mais non  
une phase  $M_1$ , à température ambiante.
3. Composition selon une des revendications 1 et 2, dans laquelle le mélange d'eau et de tensioactif  
possède un point de trouble supérieur à 30 °C.
- 55 4. Composition selon la revendication 3, dans laquelle le mélange de tensioactif et d'eau possède un point  
de trouble supérieur à 40 °C.

5. Composition selon l'une quelconque des revendications qui précèdent, dans laquelle le mélange de tensioactif et d'eau possède un point de trouble inverse inférieur à 30 °C.
6. Composition selon la revendication 5, dans laquelle le mélange de tensioactif et d'eau possède un point  
5 de trouble inverse inférieur à 10 °C.
7. Composition selon l'une quelconque des revendications qui précèdent, dans laquelle le tensioactif est présent à une concentration supérieure à 5 % en poids de la composition.
8. Composition selon la revendication 7, dans laquelle le tensioactif est présent dans une proportion  
10 comprise entre 7 et 50 % en poids de la composition.
9. Composition selon l'une quelconque des revendications qui précèdent, dans laquelle le tensioactif comprend un ou plusieurs alcools gras moyens en C<sub>10</sub> à C<sub>20</sub> alcoylés avec 5 à 15 groupes  
15 éthylèneoxy et/ou propylèneoxy.
10. Composition selon l'une quelconque des revendications qui précèdent, dans laquelle le tensioactif comprend un alkyl(en C<sub>10</sub>-C<sub>14</sub>)benzènesulfonate d'amine en C<sub>1</sub>-C<sub>6</sub>.
11. Composition selon la revendication 10, dans laquelle ladite amine en C<sub>1</sub>-C<sub>6</sub> est l'isopropylamine ou la  
20 triéthanolamine.
12. Composition selon l'une quelconque des revendications qui précèdent, comprenant un mélange de tensioactifs possédant un paramètre de solubilité moyen compris entre 10 et 13.
13. Composition selon la revendication 12, dans laquelle lesdits tensioactifs possèdent un paramètre de  
25 solubilité moyen compris entre 11 et 12.
14. Composition selon l'une quelconque des revendications qui précèdent, comprenant un mélange d'un  
30 tensioactif possédant un paramètre de solubilité supérieur à 12 et d'un tensioactif avec un paramètre de solubilité inférieur à 11.
15. Composition selon l'une quelconque des revendications qui précèdent, comprenant un tensioactif  
35 présentant une solubilité dans l'eau inférieure à 1 % en poids et un co-tensioactif en concentration suffisante pour le solubiliser jusqu'à au moins 5 % en poids.

40

45

50

55